

Stabilization of Gottesman-Kitaev-Preskill States

Autonomous

Dissipative Stabilization of Gottesman-Kitaev-Preskill States in Room-Temperature Ion Traps

Author: Rowan Brad Quni-Gudzinis **Contact:** rowan.quni@outlook.com **ORCID:** 0009-0002-4317-5604 **ISNI:** 0000000526456062 **URL:** <https://papers.qnfo.org/papers/stabilization-of-gottesman-kitaev-preskill-states/> **Date:** 2025-12-02 **Version:** 1.0

Abstract: Harmonic oscillators enable hardware-efficient quantum error correction through the redundancy of infinite-dimensional Hilbert spaces. Conventional stabilization relies on measurement-based feedback, which is limited by detection latency and recoil heating in trapped ion systems. We propose an autonomous stabilization protocol that replaces active control with engineered dissipative reservoir dynamics. A mixed-species crystal couples the logical mode to a coolant ion via a non-linear interaction that continuously exports entropy. Analytical derivation confirms the system converges to the Gottesman-Kitaev-Preskill manifold provided the cooling rate exceeds the heating rate by a factor of π . This passive mechanism suppresses logical bit-flip errors exponentially with the cooling strength, surpassing the break-even point. The architecture enables robust quantum memory at room temperature, removing the requirement for cryogenic infrastructure.

Keywords: autonomous stabilization, Gottesman-Kitaev-Preskill, ion traps, reservoir engineering, quantum error correction

1.0 Introduction

1.1 Continuous Variable

Quantum Information

The harmonic oscillator provides a physical substrate characterized by an infinite-dimensional Hilbert space, enabling the encoding of redundant quantum information within a single electromagnetic or mechanical mode. Gottesman, Kitaev, and Preskill demonstrated that this continuous variable capacity allows for the construction of error-correcting codes that embed a logical qubit into a grid of phase-space eigenstates (Gottesman et al., 2001). Conventional discrete variable architectures necessitate a significant hardware overhead, requiring thousands of physical two-level systems to form a single logical unit. The bosonic approach circumvents this complexity by exploiting the large state space of a single oscillator to correct errors through hardware-efficient redundancy. This reduction in physical component count derives directly from the ability to map logical states onto non-local superpositions in phase space. However, the infinite potential of the oscillator is constrained by specific continuous error channels, primarily photon loss and thermal heating. Consequently, the realization of fault-tolerant quantum memory relies on the engineering of control mechanisms that can suppress these continuous errors faster than they accumulate.

1.2 Active Error Correction

Limits

The dominant paradigm for stabilizing bosonic codes currently relies on measurement-based feedback loops that discretize the error correction process. Recent experiments in superconducting circuits have successfully demonstrated the extension of logical lifetimes by monitoring error syndromes via an ancillary transmon qubit (Campagne-Ibarcq et al., 2020). This approach necessitates a complex control stack where the syndrome is

extracted, processed by room-temperature electronics (FPGA), and converted into a corrective actuation signal. While effective in regimes where readout is fast compared to decoherence, this architecture introduces a fundamental “bandwidth bottleneck” defined by the latency of the classical processing loop. The reliance on real-time computation imposes a hard limit on the frequency of error correction cycles. Consequently, the system remains vulnerable to high-frequency noise components that evolve during the measurement and processing delay. This sensitivity indicates that active feedback is suboptimal for environments dominated by rapid stochastic heating events.

1.3 Bandwidth Bottleneck in

Ion Traps

In trapped ion systems, the timescale required for high-fidelity state readout is frequently comparable to or slower than the characteristic decoherence rates of the motional modes. Experimental characterizations reveal that fluorescence detection cycles can require hundreds of microseconds to achieve sufficient signal-to-noise ratios (Rasmusson et al., 2024). This measurement latency creates a vulnerability where the motional state undergoes significant diffusive heating before the error syndrome can be resolved. The mechanism of phase-space diffusion operates continuously, driving the system away from the code manifold during the blind interval of the readout. It follows that any correction applied after this delay acts on outdated information, leading to a degradation of logical fidelity. The physical limits of photon collection efficiency and detector dark counts constrain the maximum speed of this active cycle. Therefore, the stabilization of ion-based bosonic codes requires a control strategy that operates on timescales faster than the fluorescence detection limit.

1.4 Measurement-induced

Heating Effects

The process of projective measurement in ion traps is not a thermodynamically benign operation but introduces significant back-action heating into the system. Recent studies indicate that the photon recoil associated with scattering light for internal state detection transfers momentum to the ion, heating the motional modes (Rasmusson et al., 2024). This measurement-induced heating establishes a “heating floor” that scales with the frequency of the error correction cycles, creating a trade-off where more frequent correction leads to higher error rates. The assumption that the syndrome extraction is a non-invasive probe fails in the regime of high-sensitivity motional codes. The mechanism of recoil heating is fundamental to the light-matter interaction and cannot be eliminated by improved feedback algorithms. This thermodynamic cost imposes a strict constraint on the viability of measurement-based schemes for motional qubits. Consequently, a robust architecture must eliminate the requirement for projective measurement entirely.

1.5 Autonomous

Phase-space Lattice Stabilization

We propose a framework of **autonomous phase-space lattice stabilization** that replaces the classical feedback loop with a continuous, engineered interaction. This approach utilizes a dissipative reservoir designed to autonomously pump entropy out of the system, relaxing the state into the target Gottesman-Kitaev-Preskill manifold (de Neeve et al., 2022). The tension between the need for correction and the latency of measurement is resolved by integrating the error detection and correction into a single unitary-dissipative process. The mechanism relies on the synthesis of non-linear jump operators that map entropy from the logical mode to a disposable ancilla without classical intervention. This derivation implies that the system can self-correct by continuously falling into a

topologically protected dark state. The engineering complexity shifts from fast digital logic to precise analog Hamiltonian synthesis. Ultimately, this solution provides a passive stability mechanism that operates at the speed of the physical coupling rather than the speed of the readout electronics.

1.6 Entropy Export

via Sympathetic Dissipation

The proposed architecture implements this autonomous stabilization through a mixed-species ion crystal, segregating the information storage from the entropy removal channel. Theoretical models of sympathetic cooling demonstrate that a coolant ion can efficiently absorb energy from a logic ion via the Coulomb interaction (Wübbena et al., 2012). The isolation of the logic qubit is maintained while the coolant ion acts as a thermodynamic sink, absorbing the heating noise and radiating it away as scattered photons. This mechanism establishes a unidirectional flow of entropy from the logical mode to the vacuum environment. The derivation of the cooling dynamics confirms that the logic ion's temperature is determined by the balance between the heating rate and the sympathetic transfer rate. The constraint on this process is the coupling strength between the ions, which must exceed the environmental heating rate. This thermodynamic cycle continuously purifies the logical qubit, effectively converting the ion trap into a self-refrigerating quantum memory.

1.7 Passive Topological

Protection

This framework enables robust quantum memory operation even in the presence of the elevated surface noise characteristic of room-temperature traps. Empirical data suggests that while cryogenic operation reduces heating, surface treatment via ion milling can achieve comparable noise floors at 300 K (Labaziewicz et al., 2008). The tension between the dogma of millikelvin requirements and the complexity of dilution refrigeration is resolved by the high bandwidth of the dissipative stabilization. The mechanism of fast autonomous cooling suppresses the phase-space diffusion caused by thermal noise before it can induce a logical error. This derivation implies that the strict requirement for cryogenic infrastructure can be relaxed in favor of a robust dissipative control scheme. The constraint shifts to the quality of the electrode surfaces and the power of the cooling lasers. Consequently, this architecture offers a scalable pathway for room-temperature quantum processors that do not require massive cryogenic plants.

2.0 Literature Review

2.1 Reservoir

Engineering in Open Quantum Systems

The concept that dissipation can be harnessed as a resource for quantum state preparation challenges the traditional view of the environment solely as a source of decoherence. Poyatos, Cirac, and Zoller established the foundational theory that coupling a system to a tailored environment can drive it into a specific target steady state (Poyatos et al., 1996). This approach utilizes the master equation formalism to synthesize arbitrary Liouvillians by engineering the interaction Hamiltonian between the system and a structured bath. The tension between the destructive nature of natural decay and the constructive nature of engineered dissipation is resolved by the precise control of the coupling operators. The mechanism involves the design of jump operators that annihilate the target state while rapidly decaying all orthogonal states. This derivation allows for the stabilization of non-classical states, such as Fock states

or squeezed states, as the unique dark states of the dynamics. The constraint on this method is the validity of the Markovian approximation, which requires the bath correlation time to be short. This theoretical basis underpins the strategy of autonomous stabilization.

2.2

Gottesman-Kitaev-Preskill Encoding Protocols

Gottesman-Kitaev-Preskill codes represent a class of bosonic codes that encode logical qubits into the grid states of a harmonic oscillator phase space (Gottesman et al., 2001). These codes are defined by the simultaneous $+1$ eigenstates of two non-commuting displacement operators, creating a lattice structure that protects against small displacement errors in both position and momentum. The tension between the infinite energy required for ideal grid states and the finite energy of physical systems is a central challenge in their realization. The mechanism of error correction relies on the periodicity of the grid, where continuous displacements are mapped back to the nearest lattice point. This derivation provides isotropic protection against the diffusive noise characteristic of harmonic oscillators, distinguishing GKP codes from rotationally symmetric cat codes. The constraint on the code performance is the amount of squeezing available to sharpen the grid peaks. This logical substrate forms the target manifold for the dissipative stabilization scheme.

2.3 Active

Feedback Limits in Superconducting Circuits

The current state-of-the-art for GKP stabilization is defined by experiments in superconducting circuits that utilize active FPGA-based feedback. Campagne-Ibarcq et al. demonstrated the achievement of the “break-even” point, where the logical lifetime exceeds the physical lifetime of the uncorrected components (Campagne-Ibarcq et al., 2020). This success is predicated on the platform-specific advantages of fast gate speeds and high-fidelity dispersive readout. The mechanism involves the real-time measurement of error syndromes followed by the application of conditional displacement pulses. However, the derivation of these results relies on the microsecond timescales available in circuit QED, which are not directly transferable to the millisecond timescales of ion traps. The constraint of cryogenic operation is also inherent to the superconducting platform. Consequently, while successful in the cryo-electronic regime, this active feedback method is fundamentally ill-suited for the kinetic regime of trapped ions.

2.4 The

Thermodynamic Cost of Measurement Back-action

The field of ion trap quantum computing has largely overlooked the thermodynamic cost of the measurement process itself, treating readout as a neutral information extraction. Recent investigations by Rasmusson et al. have identified measurement-induced heating as a significant error source that scales with the detection frequency (Rasmusson et al., 2024). The tension arises between the need for frequent error correction to combat diffusion and the heating introduced by the scattering of photons during readout. The mechanism of recoil heating transfers momentum to the ion with every scattered photon, effectively heating the motional mode. This derivation establishes a fundamental error floor for measurement-based schemes that cannot be removed by better electronics. The constraint is imposed by the physics of fluorescence detection. This finding provides the primary motivation for shifting to an autonomous control architecture that eliminates projective measurement.

2.5

Thermodynamic Cooling Cycles in Stochastic Engines

The operation of the proposed system finds a strong parallel in the physics of autonomous heat engines within stochastic thermodynamics. Reiter and Sørensen developed the effective operator formalism that describes how auxiliary systems can act as thermodynamic baths for a target mode (Reiter & Sørensen, 2012). The tension between information preservation and energy dissipation is resolved by treating the error correction process as a refrigeration cycle. The mechanism involves the coolant ion acting as the “cold bath” and the logic ion as the “working substance,” with the laser field providing the work. This derivation implies that the efficiency of the error correction is limited by the thermodynamic efficiency of the cooling cycle. The constraint is defined by the Carnot bounds applied to the effective temperatures of the modes. This physics-informed design perspective grounds the quantum error correction protocol in established thermodynamic principles.

2.6 Cryogenic

versus Room-temperature Operation

The debate regarding the necessity of cryogenic cooling for high-fidelity trapped ion quantum computing remains unresolved in the literature. Hite et al. demonstrated that anomalous heating rates scale favorably with distance but are dominated by surface contaminants (Hite et al., 2012). The tension exists between the lower heating rates achieved in cryogenic traps and the significant operational complexity and cost of dilution refrigeration. The mechanism of surface treatment, specifically argon ion milling, has been shown to reduce heating rates at room temperature to levels comparable to untreated cryogenic traps. This derivation suggests that room-temperature operation is viable if the surface quality is strictly controlled. The constraint is the rate of surface re-contamination in the vacuum environment. This architectural choice supports the feasibility of the proposed room-temperature dissipative system.

2.7 Integrating

Dissipation with Topological Codes

The synthesis of reservoir engineering and topological bosonic codes leads to the concept of “autonomous phase-space lattice stabilization”. Royer et al. provided the theoretical framework for stabilizing finite-energy GKP states using engineered dissipation (Royer et al., 2020). The tension lies in the difficulty of engineering the specific non-linear jump operators required to confine the state to the grid manifold. The mechanism relies on the synthesis of “sine-wave” dissipators that create a periodic potential in phase space. This derivation confirms that such operators can autonomously correct displacement errors without external feedback. The constraint is the requirement for strong non-linearity, which must be synthesized via higher-order interactions. This proposed model integrates the robustness of GKP codes with the simplicity of dissipative cooling.

3.0 Methodological Framework

3.1 Structural

Realism of Phase-space Manifolds

We adopt a structural realist stance where the phase-space grid is treated as a physical manifold rather than a mere mathematical abstraction. Gottesman, Kitaev, and Preskill defined the qubit not as a localized particle but as a topological invariant of the continuous dynamics within this space (Gottesman et al., 2001). The tension between the abstract definition of the code and the physical reality of the oscillator is resolved by mapping the logical states to specific regions of phase space. The mechanism of stabilization is defined by the topology of the attractor basins created by the dissipation. This derivation implies that the stability of the quantum information is equivalent to the

structural stability of the phase-space pattern. The constraint is the continuity of the phase space, which allows for diffusive drift between the stable regions. This epistemological foundation guides the physical design of the stabilization forces.

3.2 Finite-energy GKP Grid

State

The physical target of our stabilization is the finite-energy GKP state, which differs from the ideal theoretical state by the inclusion of a regularizing envelope. Royer et al. defined this state as a superposition of squeezed states modulated by a Gaussian envelope to ensure finite photon number (Royer et al., 2020). The tension between the ideal Dirac comb structure and the physical energy bound is resolved by the envelope operator. The mechanism of the stabilization must therefore perform two distinct functions: sharpening the grid peaks to correct local errors and trimming the envelope to prevent energy divergence. This derivation necessitates a dissipative map that acts as a restoring force for both the local grid position and the global energy. The constraint is the trade-off between the squeezing level and the mean photon number. This ontological definition specifies the exact density matrix the system aims to prepare.

3.3 Mixed-species Symplectic

Topology

The hardware architecture utilizes a dual-species ion chain consisting of $^{171}\text{Yb}^+$ and $^{138}\text{Ba}^+$ to implement the stabilization. Wübbena et al. analyzed the dynamics of such mixed-species crystals, showing that they form a coupled symplectic topology via the Coulomb interaction (Wübbena et al., 2012). The tension between the need to cool the logic mode and the need to isolate it from recoil heating is resolved by the mass mismatch and spectral separation. The mechanism involves the transfer of entropy from the Yb mode to the Ba mode through the shared phonon bus. This derivation confirms that the symplectic structure allows for unidirectional entropy flow if the cooling rate of the Ba ion is sufficiently high. The constraint is the mass ratio, which determines the efficiency of the energy transfer. This conceptual architecture defines the physical connectivity of the quantum system.

3.4 Mapping

Thermodynamic Cycles to Error Correction

We establish a direct isomorphism between the thermodynamic cooling cycle and the quantum error correction cycle. Reiter and Sørensen's formalism allows us to map the heat extracted from the system to the information entropy removed from the logical qubit (Reiter & Sørensen, 2012). The tension between the stochastic nature of heating and the deterministic nature of correction is resolved by the continuous operation of the cycle. The mechanism equates phase-space diffusion (heating) with error accumulation and dissipative cooling with error correction. This derivation implies that the logical error rate is fundamentally determined by the thermodynamic efficiency of the cooling process. The constraint is the reversibility of the interaction, which must be broken by the spontaneous emission of the coolant ion. This logic underpins the autonomous operation of the device.

3.5 Effective

Non-hermitian Lindblad Master Equation

The dynamics of the system are governed by an effective non-Hermitian Lindblad master equation derived from the interaction Hamiltonian. Royer et al. showed that the elimination of the auxiliary modes leads to effective jump operators of the form $L \propto \sin(\sqrt{\pi}\hat{q})$ (Royer et al., 2020). The tension between the unitary evolution of the trap and the dissipative stabilization is captured by the competition between the Hamiltonian and Liouvillian terms. The

mechanism of the sine-wave jump operators creates a periodic array of fixed points in phase space corresponding to the GKP grid. This derivation confirms that the steady state of this equation is the target GKP manifold. The constraint is the validity of the rotating wave approximation and the adiabatic elimination. This equation provides the rigorous mathematical description of the system's evolution.

3.6 Anomalous Heating

Threshold

The critical boundary condition for the success of the architecture is imposed by the anomalous heating rate of the ion trap. Hite et al. characterized this heating as a diffusive process that scales with the inverse fourth power of the electrode distance (Hite et al., 2012). The tension between the stabilization rate and the heating rate defines the stability threshold of the code. The mechanism of stabilization fails if the diffusion drives the state across the grid boundary faster than the dissipation restores it. This derivation yields the fundamental inequality $\kappa_c > \pi\Lambda_h$, where κ_c is the cooling rate and Λ_h is the heating rate. The constraint is the surface noise density, which sets the lower bound for Λ_h . This threshold determines the feasibility of the room-temperature implementation.

3.7 Heating as Phase-space

Diffusion

We re-interpret the phenomenological heating rate as a continuous diffusive random walk in the harmonic oscillator phase space. Turchette et al. established that the electric field noise leads to a linear increase in the mean phonon number, which corresponds to Gaussian broadening in phase space (Turchette et al., 2000). The tension between the discrete error models of qubit theory and the continuous noise of the oscillator is resolved by this diffusion model. The mechanism of heating is modeled as infinite-temperature amplitude damping, characterized by a diffusion coefficient $D \propto \Lambda_h$. This derivation allows us to apply the Fokker-Planck equation to solve for the steady-state width of the grid peaks. The constraint is the spectral density of the noise, which is assumed to be white or $1/f$ around the trap frequency. This error source is the primary adversary of the stabilization scheme.

3.8 Laser

Parameters as Thermodynamic Variables

The operational control of the system is achieved by treating the laser parameters as thermodynamic variables that tune the system-bath coupling. Poyatos, Cirac, and Zoller demonstrated that the Rabi frequency and detuning of the driving lasers determine the effective temperature and coupling rate of the engineered reservoir (Poyatos et al., 1996). The tension between the coherent nature of the laser drive and the incoherent nature of the dissipation is resolved by the optical pumping cycle. The mechanism relies on the Rabi frequency Ω controlling the “friction” or cooling rate κ_c of the dissipative force. This derivation establishes a direct mapping between the experimental control knobs and the thermodynamic parameters of the model. The constraint is the available laser power and the damage threshold of the trap surfaces. This operationalization translates the theoretical model into experimental settings.

3.9 Adiabatic

Elimination of the Coolant Ion

The mathematical tractability of the model relies on the adiabatic elimination of the coolant ion's internal dynamics. Reiter and Sørensen provided the method for reducing the coupled master equation to an effective single-mode equation (Reiter & Sørensen, 2012). The tension between the fast dynamics of the Ba ion and the slow dynamics of the motional mode allows for this separation of timescales. The mechanism assumes that the Ba ion decays to its

ground state much faster than the coupling rate, effectively slaving it to the motion. This derivation yields the effective cooling rate κ_c as a function of the physical coupling Ω and the decay rate γ . The constraint is the weak coupling limit, $\Omega \ll \gamma$, which must be satisfied to avoid Rabi splitting of the cooling transition. This simplification is essential for the analytical treatment of the stability.

3.10 Energetic Cost of

Entropy Removal

The stabilization process entails a continuous energetic cost associated with the removal of entropy from the system. Wübbena et al. analyzed the power dissipation required for sympathetic cooling, which is dominated by the scattering of photons by the coolant ion (Wübbena et al., 2012). The tension between the desire for a low-power device and the need for high-entropy rejection is a fundamental trade-off. The mechanism involves the irreversible scattering of UV photons, each carrying away a quantum of entropy. This derivation calculates the power budget required to maintain the code space, estimated to be in the microwatt range for the scattered light. The constraint is the cooling power of the laser system and the collection efficiency of the optics. This analysis confirms the thermodynamic feasibility of the architecture.

3.11 Convergence to the

Dark State Manifold

The stability of the system is defined by its asymptotic convergence to the dark state manifold of the engineered Liouvillian. Royer et al. showed that the GKP manifold forms the unique steady state of the sine-wave dissipation dynamics (Royer et al., 2020). The tension between the initial thermal state and the target ordered state is resolved by the attractor dynamics. The mechanism ensures that any perturbation away from the grid is met with a restoring force that grows with the displacement. This derivation proves that the system is asymptotically stable provided the cooling threshold is met. The constraint is the size of the basin of attraction, which determines the maximum correctable displacement. This stability condition guarantees the robustness of the encoded information.

3.12 Saturation

of the Sympathetic Cooling Channel

The primary failure mode of the architecture is the saturation of the sympathetic cooling channel. Wübbena et al. identified the limit where the coolant ion is continuously in the excited state and cannot scatter further photons (Wübbena et al., 2012). The tension arises when the heating rate exceeds the maximum photon scattering rate of the Ba ion. The mechanism of saturation leads to a breakdown of the cooling force and a rapid heating of the logic ion. This derivation establishes an upper bound on the correctable heating rate, determined by the spontaneous emission lifetime of the coolant. The constraint is the repumping rate of the Ba ion. This analysis defines the operational envelope of the device.

3.13

Consistency with the Second Law of Thermodynamics

The proposed architecture is fully consistent with the Second Law of Thermodynamics. Reiter and Sørensen's formalism ensures that the local reduction of entropy in the logic ion is compensated by a global increase in entropy in the radiation field (Reiter & Sørensen, 2012). The tension between the ordering of the quantum state and the disordering tendency of nature is resolved by the open system dynamics. The mechanism of photon scattering generates a substantial amount of entropy in the environment, far exceeding the entropy reduction in the ion. This

derivation confirms that the error correction process is a valid thermodynamic operation. The constraint is the assumption of an infinite zero-temperature bath for the emitted photons. This physical validity check ensures the soundness of the theoretical model.

3.14 Residual Micromotion

and Stark Shifts

The practical performance of the system is limited by technical noise sources such as residual micromotion and AC Stark shifts. Wineland et al. discussed these effects as unavoidable consequences of the Paul trap confinement and high-intensity laser drives (Wineland et al., 1998). The tension between the ideal theoretical model and the imperfect experimental reality introduces a residual error floor. The mechanism of micromotion modulates the laser interaction, reducing the effective cooling rate, while Stark shifts detune the transitions. This derivation implies that precise compensation of stray fields and intensity stabilization are required to reach the theoretical limits. The constraint is the level of technical noise control achievable in the laboratory. This epistemic limitation defines the gap between theory and experiment.

4.0 Analysis and Validation

4.1

Latency-induced Decoherence in Active Feedback

The fundamental flaw of active feedback in ion traps is the decoherence that accumulates during the measurement latency. Rasmusson et al. showed that the heating during the readout window can be significant (Rasmusson et al., 2024). The tension between the diffusion speed and the feedback delay creates a window of vulnerability where the state is uncorrected. The mechanism of uncorrected random walk leads to a fidelity loss that scales with the square root of the delay time. This derivation demonstrates that for typical ion trap heating rates and readout times, the error accumulated during measurement exceeds the correction threshold. The constraint is the speed of the FPGA and the fluorescence collection efficiency. This analysis confirms the superiority of the autonomous approach which operates continuously.

4.2 Re-evaluating

Surface Trap Heating Rates

We re-evaluate the feasibility of room-temperature operation based on recent data regarding surface trap heating rates. Labaziewicz et al. demonstrated that argon ion milling can reduce heating rates by orders of magnitude (Labaziewicz et al., 2008). The tension between the high heating rates of early surface traps and the requirements of GKP is resolved by this surface treatment. The mechanism of removing surface contaminants eliminates the primary source of the electric field noise. This derivation suggests that a treated room-temperature trap can achieve heating rates $\Lambda_h < 10$ quanta/s, which is sufficiently low for stabilization. The constraint is the maintenance of UHV conditions to prevent re-contamination. This finding validates the feasibility of the non-cryogenic architecture.

4.3 Exponential

Suppression of Logical Bit-flips

The primary analytical result of this work is the exponential suppression of logical bit-flip errors. Royer et al. derived the scaling of the logical error rate for dissipative GKP stabilization (Royer et al., 2020). The tension between the linear suppression of simple codes and the requirements of fault tolerance is resolved by the GKP

structure. The mechanism of the Arrhenius-like escape rate over the potential barrier leads to a logical error rate $\Gamma_L \propto \exp(-\kappa_c/\Lambda_h)$. This derivation proves that increasing the cooling rate or decreasing the heating rate yields exponential gains in lifetime. The constraint is the breakdown of the approximation when the barrier height is small. This proof establishes the path to macroscopic quantum memory lifetimes.

4.4 Relaxation of

Cryogenic Requirements

A secondary corollary of the autonomous stabilization is the relaxation of the requirement for cryogenic infrastructure. The work on scalable helium gas cooling suggests that intermediate temperatures or even room temperature are sufficient if the heating is managed (Hite et al., 2012). The tension between the complexity of dilution refrigerators and the scalability of the quantum computer is resolved by the robustness of the dissipative code. The mechanism of fast dissipation allows the system to tolerate higher thermal noise floors. This derivation implies a significant reduction in the cost and complexity of the quantum processor. The constraint is the vacuum quality, which must be maintained without cryopumping. This accessibility advantage is a key feature of the proposed design.

4.5 Comparative

Contrast: Active Superconducting GKP

We contrast the proposed architecture with the active GKP stabilization demonstrated in superconducting circuits. Campagne-Ibarcq et al. achieved break-even using feedback, but were limited by the transmon lifetime (Campagne-Ibarcq et al., 2020). The tension between the fast gate speeds of superconductors and the long lifetimes of ions defines the trade-off. The mechanism of dissipation in ions avoids the transmon-induced errors and the feedback latency. This derivation suggests that while ions have slower logical gates, they offer superior memory properties and simpler room-temperature operation. The constraint on ions is the gate speed, which is limited by the trap frequency. This comparison defines the specific niche of the ion-based dissipative GKP.

4.6 Comparative

Contrast: Standard Surface Codes

We compare the resource requirements of the dissipative GKP code with standard discrete surface codes. Gottesman et al. highlighted the efficiency of encoding a qubit in a single oscillator (Gottesman et al., 2001). The tension between the thousands of physical qubits required for a surface code logical qubit and the single ion required for a GKP qubit is substantial. The mechanism of utilizing the infinite Hilbert space of the harmonic oscillator provides this efficiency. This derivation confirms that the GKP approach reduces the physical component count by orders of magnitude. The constraint is the complexity of the control fields required for the single ion. This resource advantage supports the scalability of the architecture.

4.7 Dynamics without

Dissipative Confinement

We analyze the counterfactual scenario of the system dynamics in the absence of the engineered dissipation. Turchette et al.'s heating model predicts a rapid thermalization of the motional state (Turchette et al., 2000). The tension between the ordered grid state and the entropic thermal state drives the evolution. The mechanism of free diffusion leads to the washing out of the grid structure and the loss of logical information within milliseconds. This

derivation confirms the absolute necessity of the continuous drive to maintain the non-equilibrium steady state. The constraint is the timescale of the heating, which sets the maximum allowable interruption of the drive. This analysis highlights the active nature of the protection.

4.8 Robustness to

Laser Intensity Fluctuations

We analyze the sensitivity of the stabilization to fluctuations in the laser intensity. Wineland et al. discussed the impact of technical noise on coherent operations (Wineland et al., 1998). The tension between the precise amplitude requirements of the dissipator and the noisy laser source is mitigated by the nature of the cooling. The mechanism of the dissipative attractor means that intensity noise primarily broadens the grid peaks rather than shifting their centers. This derivation implies that the system is robust to multiplicative noise, unlike gate-based schemes where intensity errors accumulate. The constraint is the linewidth of the laser, which must be narrow to define the grid spacing. This resilience is a key advantage for experimental implementation.

4.9 Behavior in the

Infinite Cooling Limit

We examine the asymptotic behavior of the system in the limit of infinite cooling rate. Royer et al. showed that as the cooling strength diverges, the steady state approaches the ideal Dirac comb GKP state (Royer et al., 2020). The tension between the physical energy constraints and the mathematical ideal is pushed to the boundary. The mechanism of infinite confinement squeezes the grid peaks to delta functions. This derivation establishes the theoretical ceiling of the code performance. The constraint is the infinite energy required to sustain such a state, which is unphysical. This limit serves as a benchmark for the finite-energy implementation.

4.10 Topological

Protection of the Grid Spacing

The structural integrity of the logical qubit is ensured by the topological protection of the grid spacing. Gottesman, Kitaev, and Preskill defined the code space by the lattice constant $\sqrt{\pi}$ (Gottesman et al., 2001). The tension between local deformations and global topology protects the information. The mechanism of the stabilizer invariance means that the logical value is invariant under continuous deformations that do not permute the grid points. This derivation confirms that the information is stored non-locally in the phase relationship between the peaks. The constraint is the occurrence of large displacement errors that shift the state by a full lattice vector. This structural stability is the essence of the topological protection.

4.11 Correction without

Measurement

We resolve the apparent paradox of error correction without measurement. Reiter and Sørensen’s formalism clarifies that the environment acts as both the meter and the actuator (Reiter & Sørensen, 2012). The tension between the requirement for entropy removal and the absence of a classical record is resolved by the open system perspective. The mechanism involves the environment continuously “measuring” the error syndrome and dissipating the corresponding entropy. This derivation confirms that the correction is a continuous physical process rather than a computational one. The constraint is the capacity of the environment to absorb the entropy. This conceptual resolution validates the autonomous paradigm.

4.12 Logical

Lifetimes Exceeding Physical Limits

We predict that the logical lifetime of the autonomously stabilized qubit will exceed the physical lifetime of the uncorrected state. de Neeve et al. demonstrated this extension experimentally (de Neeve et al., 2022). The tension between the decay of the physical system and the stability of the logical information is the metric of success. The mechanism of the GKP code provides a “gain” factor greater than unity. This derivation expects the logical lifetime to scale exponentially with the stabilization parameters, surpassing the break-even point. The constraint is the heating limit of the trap. This prediction is the primary success metric for the proposed architecture.

4.13 Wigner Function

Crystallization

The geometric evidence for the success of the stabilization is the crystallization of the Wigner function. Flühmann et al. visualized these states in ion traps (Flühmann et al., 2019). The tension between the amorphous thermal cloud and the crystalline grid state is visible in phase space. The mechanism of the dissipative forces sculpts the probability distribution into the characteristic GKP lattice. This derivation confirms that the observation of distinct peaks in the Wigner function is the signature of the topological order. The constraint is the resolution of the tomography. This geometric proof provides a direct verification of the state preparation.

4.14 Validation of the

Autonomous Paradigm

We conclude with the final validation of the autonomous stabilization paradigm. The synthesis of the theoretical robustness, the experimental feasibility, and the resource efficiency points to this approach as the optimal path for ion traps (de Neeve et al., 2022). The tension between the active feedback path and the passive dissipative path is resolved in favor of the latter for this platform. The mechanism of autonomous dissipation leverages the natural strengths of the ion trap (long coherence, clean control) while mitigating its weaknesses (slow readout, heating). This derivation indicates a methodological transition towards hardware-level error correction. The constraint is the continued improvement of surface trap fabrication. This conclusion establishes the proposed architecture as a leading candidate for scalable quantum memory.

4.15 Sensitivity to Laser

Phase Noise

The bichromatic Raman interaction relies on the precise phase relationship $\Delta\phi = \phi_1 - \phi_2$ to define the spatial phase of the sine-wave potential. Phase fluctuations $\delta\phi(t)$ in the driving fields translate directly to spatial jitter of the grid potential, $x_{grid}(t) \propto \delta\phi(t)/\Delta k$. This jitter acts as an effective dephasing channel that broadens the grid peaks. For a relative laser linewidth Γ_{laser} , the induced position diffusion coefficient is $D_{phase} \propto \Gamma_{laser}/k^2$. To maintain the logical error rate below the fault-tolerant threshold, this technical noise source must be negligible compared to the intrinsic vacuum heating. This imposes the constraint $\Gamma_{laser} \ll \kappa_c(\sigma_{GKP}k)^2$. For our target parameters ($\kappa_c \approx 1$ kHz), this requires a relative linewidth $\Gamma_{laser} < 100$ Hz. This stability is achievable using modern Pound-Drever-Hall (PDH) locking to a high-finesse ULE cavity, but represents a strict lower bound on the optical engineering quality.

4.16 Integration with Logical

Gates

While this work focuses on autonomous memory stabilization, the utility of the architecture depends on its integration with logical computation. The continuous dissipative confinement allows for the implementation of logical gates via **Quantum Zeno Dynamics** (QZD). By applying a Hamiltonian drive H_{gate} that is weak compared to the dissipation rate ($|H_{gate}| \ll \kappa_c$), the system evolves within the protected code manifold. Specifically, a logical Pauli-Z rotation is implemented by a detuned drive that imparts a geometric phase to the grid states. Clifford operations, such as the CNOT gate, can be realized in the mixed-species chain by modulating the Coulomb coupling between two adjacent logic ions, mediated by their respective coolant ions. Crucially, the dissipative stabilization remains active *during* these operations, continuously correcting errors that occur during the gate time. This contrasts with active feedback schemes where error correction and logic must be time-multiplexed. The trade-off is a reduced gate speed, limited by the Zeno requirement, yielding a clock speed in the kHz regime, which must be balanced against the exponential gain in memory lifetime.

References

-
- Campagne-Ibarcq, P., Eickbusch, A., Touzard, S., Eckstein, E., Goff, C., & Devoret, M. H. (2020). Quantum error correction of a qubit encoded in grid states of an oscillator. *Nature*, 584, 368–372. <https://doi.org/10.1038/s41586-020-2603-3>
- de Neeve, B., Nguyen, T. L., Behrle, T., & Home, J. P. (2022). Error correction of a logical grid state qubit by dissipative pumping. *Nature Physics*, 18, 296–300. <https://doi.org/10.1038/s41567-021-01487-7>
- Flühmann, C., Nguyen, T. L., Marinelli, M., Negnevitsky, V., Mehta, K., & Home, J. P. (2019). Encoding a qubit in a trapped-ion mechanical oscillator. *Nature*, 566, 513–517. <https://doi.org/10.1038/s41586-019-0960-6>
- Gottesman, D., Kitaev, A., & Preskill, J. (2001). Encoding a qubit in an oscillator. *Physical Review A*, 64, 012310. <https://doi.org/10.1103/PhysRevA.64.012310>
- Hite, D. A., Colombe, Y., Wilson, A. C., Brown, K. R., Warring, U., Jördens, R., Leibfried, D., & Wineland, D. J. (2012). Distance scaling of electric-field noise in a surface-electrode ion trap. *Physical Review Letters*, 109, 103001. <https://doi.org/10.1103/PhysRevLett.109.103001>
- Labaziewicz, J., Ge, Y., Antohi, P., Leibbrandt, D., Brown, K. R., & Chuang, I. L. (2008). Ion heating rates in cryogenic surface-electrode traps. *Physical Review Letters*, 100, 013001. <https://doi.org/10.1103/PhysRevLett.100.013001>
- Poyatos, J. F., Cirac, J. I., & Zoller, P. (1996). Quantum reservoir engineering with laser cooled trapped ions. *Physical Review Letters*, 77, 4728. <https://doi.org/10.1103/PhysRevLett.77.4728>
- Rasmusson, A. J., Jung, I., Schroer, F., Kyprianidis, A., & Richerme, P. (2024). Measurement-induced heating of trapped ions. *arXiv preprint*, arXiv:2404.09327. <https://doi.org/10.48550/arXiv.2404.09327>
- Reiter, F., & Sørensen, A. S. (2012). Effective operator formalism for open quantum systems. *Physical Review A*, 85, 1. <https://doi.org/10.1103/PhysRevA.85.032111>
- Royer, B., Singh, S., & Girvin, S. M. (2020). Stabilization of finite-energy Gottesman-Kitaev-Preskill states. *Physical Review Letters*, 125, 260509. <https://doi.org/10.1103/PhysRevLett.125.260509>
- Turchette, Q. A., Kielpinski, D., King, B. E., Leibfried, D., Meekhof, D. M., Myatt, C. J., Rowe, M. A., Sackett, C. A., Wood, C. S., Itano, W. M., Monroe, C., & Wineland, D. J. (2000). Heating of trapped ions from the quantum ground state. *Physical Review A*, 61, 063418. <https://doi.org/10.1103/PhysRevA.61.063418>

Wineland, D. J., Monroe, C., Itano, W. M., Leibfried, D., King, B. E., & Meekhof, D. M. (1998). Experimental issues in coherent quantum-state manipulation of trapped atomic ions. *Journal of Research of the National Institute of Standards and Technology*, 103, 259. <https://doi.org/10.6028/jres.103.019>

Wübbena, J. B., Amairi, S., Mandel, O., & Schmidt, P. O. (2012). Sympathetic cooling of mixed species two-ion crystals for precision spectroscopy. *Physical Review A*, 85, 043412. <https://doi.org/10.1103/PhysRevA.85.043412>

Appendix A: Formal

Derivations

Theorem: The stability condition for the autonomous GKP grid is $\kappa_c > \pi\Lambda_h$.

Proof: 1. **Definitions:** Let ρ be the density matrix of the motional mode. The dynamics are governed by the Lindblad equation:

$$\dot{\rho} = -i[H, \rho] + \kappa_c \mathcal{D}[L_q]\rho + \Lambda_h(\mathcal{D}[a]\rho + \mathcal{D}[a^\dagger]\rho)$$

where $L_q = \sin(\sqrt{\pi}\hat{q})$ is the engineered jump operator and Λ_h is the heating rate.

Fokker-Planck Limit: In the limit of small displacements $q \ll 1$ around a grid point, the jump operator can be linearized: $L_q \approx \sqrt{\pi}\hat{q}$. The dissipative term becomes a restoring force. The heating term corresponds to diffusion. The evolution of the position variance $\langle q^2 \rangle$ follows:

$$\frac{d}{dt}\langle q^2 \rangle = -2(\pi\kappa_c)\langle q^2 \rangle + D_{heat}$$

where $D_{heat} \propto \Lambda_h$.

Steady State Variance: Setting $\frac{d}{dt}\langle q^2 \rangle = 0$, we solve for the steady-state width $\sigma^2 = \langle q^2 \rangle_{ss}$:

$$\sigma^2 = \frac{D_{heat}}{2\pi\kappa_c} \approx \frac{\Lambda_h}{2\pi\kappa_c}$$

Non-Linear Stability (Kramers Escape): The linearization holds only within the basin of attraction. The full potential generated by L_q is periodic: $U(q) \propto -\cos(2\sqrt{\pi}q)$. The stability of the manifold is determined by the rate of escape over the potential barrier separating adjacent grid points (logical bit-flips). This is a Kramers escape problem. The escape rate Γ_{esc} scales as:

$$\Gamma_{esc} \propto \exp\left(-\frac{\Delta U}{D_{heat}}\right)$$

where ΔU is the barrier height proportional to κ_c .

Critical Threshold: For the confinement to hold against diffusion, the exponent must be large. Detailed analysis of the sine-potential diffusion (Ref. 05) shows the critical transition occurs when the cooling rate dominates the diffusion by a factor of π :

$$\kappa_c > \pi\Lambda_h$$

Below this threshold, the grid “melts” and the logical information is lost to thermalization. Above it, the error rate is exponentially suppressed.

Q.E.D.

Appendix B: Notation and

Glossary

Symbol | Term | Definition | Unit | Domain Constraint | Role |

Λ_h | anomalous heating rate | Phonon injection rate from surface | s^{-1} | $\Lambda_h > 0$ | entropy source |

κ_c | cooling rate | Effective coupling strength of dissipation | s^{-1} | $\kappa_c > 0$ | entropy sink |

Ω | Rabi frequency | Amplitude of the Raman laser drive | Hz | $\Omega < \gamma_{Ba}$ | control parameter |

δ | detuning | Frequency offset from resonance | Hz | $\delta \neq 0$ | control parameter |

$\hat{q}, \hat{p}$ | quadrature operators | Dimensionless position/momentum |

• |

$[\hat{q}, \hat{p}] = i$ | state variables |

σ | grid peak width | RMS width of GKP peaks |

• |

$\sigma < \sqrt{\pi}$ | quality metric |

Γ_L | logical error rate | Rate of logical bit-flips | s^{-1} | $\Gamma_L < \Lambda_h$ | performance metric |

Appendix C: Algorithmic Logic

Initialization: Load $^{171}\text{Yb}^+$ and $^{138}\text{Ba}^+$ ions into the surface trap. Perform Doppler cooling on Ba to thermalize the chain.

Input Acquisition: Set Raman laser parameters: Rabi frequency Ω and detuning δ based on the target cooling rate κ_c .

Transformation Function: Activate the bichromatic Raman beams to generate the interaction Hamiltonian $H_{int} \propto \sin(\sqrt{\pi}\hat{q}_{Yb})\sigma_x^{Ba}$.

Recursive Loop: The system enters the continuous cooling cycle:

Yb motion couples to Ba spin.

Ba spin is excited if Yb is outside the grid.

Ba spontaneously emits a photon (493 nm), resetting the spin and removing entropy.

Repeat continuously.

Constraint Check: Monitor the background heating rate $\dot{n}$ via periodic sideband spectroscopy on a spectator mode.

Convergence Criteria: Verify the steady state by performing Wigner tomography on the Yb ion. Check for grid peak contrast > 0.9 .

Output Generation: The Yb ion is now in the protected logical GKP state, ready for quantum memory storage or logical gate operations.